




# Double row angular contact


**JESA.**  
bearing solutions



offen




Z



2Z



RS



2RS

## Dimensions (mm):

d	D	B
De 2 à 17	De 30 à 47	De 14.3 à 22.2

## Double-row angular contact ball bearings JESA

Dimensions				Abbreviations and versions					Basic loads		Speed limit		Dimensions		Unit weight in kg
d	D	B	rs min	Open version	One (Z) flange	Two (2Z) flanges	One (RS) seal	Two (2RS) seals	C, dyn. N	Cor stat. N	Grease	Oil	da min	Da max	
10	30	14,3	0,6	3200	3200 Z	3200 2Z	3200 RS	3200 2RS	7000	3800	14000	19000	14	26	0,049
12	32	15,9	0,6	3201	3201 Z	3201 2Z	3201 RS	3201 2RS	9150	5050	13000	17000	16	28	0,057
15	35	15,9	0,6	3202	3202 Z	3202 2Z	3202 RS	3202 2RS	10000	6050	11000	15000	19	31	0,064
	42	19	1	3302	3302 Z	3302 2Z	3302 RS	3302 2RS	17200	10100	9900	13000	20	37	0,132
17	40	17,5	0,6	3203	3203 Z	3203 2Z	3203 RS	3203 2RS	13200	8150	11000	14000	21	36	0,091
	47	22,2	1	3303	3303 Z	3303 2Z	3303 RS	3303 2RS	20400	12100	9000	12000	22	42	0,181

